



# DERAY®-HXKT







## -55° to +110° C

Semi-rigid



Heat-shrinkable sleeve –  
Modified polyethylene  
Radiation crosslinked  
With polyolefin based  
melttable adhesive

**Don't worry, avoid creeping damp. DERAY-HXKT** is a semi-rigid, non-melttable heat-shrinkable sleeve with an adhesive inner lining and high shrinking abilities which guarantee high temperature resistance, moisture-resistant sealing, bending protection and strain relief. Sensitive components and connectors are encapsulated by this sleeve, ensuring faultless function and protection with regard to environmental influences.

Ordering size  in inches	Diameter as supplied  d4 min. mm	Diameter fully recovered  d3 max. appr. mm	Wall thickness of adhesive fully recovered  S 3 appr. mm	Wall thickness overall fully recovered  S 5 appr. mm	Weight  max. g/m	Delivery units		
						lengths of 1,22 m m	spool m	mini spool m
1/8	3.2	0.8	0.40	0.90	5.4	30.5	300	–
3/16	4.8	1.5	0.80	1.40	10.1	30.5	300	–
1/4	6.4	2.0	0.75	1.40	13.1	12.2	300	–
3/8	9.5	3.4	1.00	1.65	20.8	12.2	150	–
1/2	12.7	5.0	1.00	1.70	30.6	12.2	100	–
3/4	19.0	8.0	1.20	1.95	53.8	12.2	50	–
1	25.4	10.2	1.20	2.00	78.5	12.2	50	–



Standard colour				
0 = black				



Remarks:  
– Cut lengths – printed on request – with a surcharge  
– Air-filled up to size 1/2"  
– Certifications available with a surcharge  
– Technical data pages 44-45  
Subject to alteration.

### Safety warning:

For work involving electric tensions of more than 48 V, insulating, connecting, repairing, and waterproofing electrical components should only be carried out by qualified electricians.