

# DERAY®-H









## -55° to +125° C

Flexible

Heat-shrinkable sleeve -  
Modified polyethylene  
Radiation crosslinked  
Insulation class E (VDE 05 30)

**Safety in concept** is offered by **DERAY-H** in cable insulating, cable marking and bundling. In addition, the flexible, non-meltable and quick-shrinking material guarantees effective electrical insulation, mechanical protection, as well as excellent corrosion protection, bending protection and strain relief. Recommended areas of application are insulating soldered terminals, cable brackets, cable clamps, bare conductors and busbars.

Ordering size	Diameter as supplied min. d2 mm	Diameter fully recovered max. d1 mm	Wall thickness as supplied S2 appr. mm	Wall thickness fully recovered S1 appr. mm	Delivery units		
					lengths of 1,22 m m	spool m	mini spool m
3/64	1.2	0.6	0.20	0.40	30.5	300	150
1/16	1.6	0.8	0.20	0.40	30.5	300	150
3/32	2.4	1.2	0.25	0.50	30.5	300	150
1/8	3.2	1.6	0.25	0.50	30.5	300	150
3/16	4.8	2.4	0.25	0.50	30.5	300	75
1/4	6.4	3.2	0.30	0.60	12.2	300	75
3/8	9.5	4.8	0.30	0.60	12.2	150	75
1/2	12.7	6.4	0.30	0.60	12.2	100	50
3/4	19.0	9.5	0.40	0.80	12.2	50	30
1	25.4	12.7	0.45	0.90	12.2	50	30
1 1/4	31.8	15.9	0.45	0.90	-	50	30
1 1/2	38.0	19.0	0.50	1.00	-	50	30
2	51.0	25.4	0.55	1.10	-	50	30
40*	4.0	1.6	0.20	0.50	-	300	-
56*	5.6	2.4	0.20	0.50	-	300	-
81*	8.1	3.2	0.20	0.60	-	300	-
110*	11.0	4.8	0.25	0.60	-	150	-
150*	15.0	6.4	0.25	0.60	-	100	-



Standard colours					
0 = black	2 = red	4 = yellow	6 = blue	9 = white	99 = transp.
spool, mini spool	mini spool				
Delivery units					

Remarks:  
 - Cut lengths - printed on request - with a surcharge  
 - Air-filled up to size 1/2"  
 - Certifications available with a surcharge  
 - Certifications possible only for sizes measured in inches  
 - Sizes marked with \* only available in black  
 - Technical data pages 40-41  
 Subject to alteration.

