



DERAY®-IAKT

-55° to +110° C*

Flexible



Heat-shrinkable sleeve –
Modified polyethylene
Radiation crosslinked
With thermoplastic adhesive

DERAY-IAKT suits moist environments. This flexible heat-shrinkable sleeve is ideal for effective moisture-resistant insulation of electrical connections, connectors, harnesses, splices and components. Its extreme shrinking abilities make it possible for this tube to shrink down on objects with a large diameter variation.

Ordering size in mm		Diameter as supplied d4 min.		Diameter fully recovered d3 max. appr. mm	Wall thickness of adhesive fully recovered S 3 appr. mm	Wall thickness overall fully recovered S 5 appr. mm	Delivery units		
3:1	4:1	mm	mm				lengths of 1,22 m	spool* m	mini spool m
3/1		3.0		1.0	0.40	1.00	30.5	300	–
4.5/1.5		4.5		1.5	0.50	1.10	30.5	300	–
6/2		6.0		2.0	0.50	1.20	12.2	300	–
9/3		9.0		3.0	0.50	1.40	12.2	150	–
12/4		12.0		4.0	0.60	1.70	12.2	100	–
19/6		19.0		6.0	0.60	2.10	12.2	50	–
24/8		24.0		8.0	0.70	2.40	12.2	50	–
40/13		40.0		13.0	0.70	2.40	12.2	30	–
	4/1		4.0	1.0	0.40	1.00	30.5	300	–
	8/2		8.0	2.0	0.50	1.20	12.2	150	–
	12/3		12.0	3.0	0.50	1.40	12.2	100	–
	16/4		16.0	4.0	0.60	1.70	12.2	50	–
	24/6		24.0	6.0	0.60	2.10	12.2	50	–
	32/8		32.0	8.0	0.70	2.40	12.2	50	–
	52/13		52.0	13.0	0.70	2.40	12.2	50	–

* spool only in black

Standard colours for lengths of 1,22m				
0 = black	99 = transparent			
●	○			



Remarks:
– Cut lengths – printed on request – with a surcharge
– Air-filled up to size 12/4 and 12/3
– Technical data pages 44-45
Subject to alteration.
*Outer Jacket

Safety warning:

For work involving electric tensions of more than 48 V, insulating, connecting, repairing, and water-proofing electrical components should only be carried out by qualified electricians.

