

DERAY®-IHKT








- 55° to + 125° C*

Flexible



Heat-shrinkable sleeve –
Modified polyethylene
Radiation crosslinked
With temperature resistant,
thermoplastic adhesive

One piece is all it takes, for short-circuits or malfunctions in electrical assembly components and connections. Due to its extreme shrinking abilities, **DERAY-IHKT** offers reliable protection. This flexible heat-shrinkable sleeve has a chemically resistant adhesive inner lining with excellent adhesive properties.

Ordering size in mm	Diameter as supplied d4 min. mm	Diameter fully recovered d3 max. appr. mm	Wall thickness of adhesive fully recovered S 3 appr. mm	Wall thickness overall fully recovered S 5 appr. mm	Weight max. g/m	Delivery units		
						lengths of 1,22 m m	spool m	mini spool m
4/1	4.0	1.0	0.40	1.00	8.2	30.5	300	–
8/2	8.0	2.0	0.40	1.20	12.2	12.2	150	–
12/3	12.0	3.0	0.40	1.40	24.8	12.2	100	–
16/4	16.0	4.0	0.60	1.70	41.8	12.2	50	–
24/6	24.0	6.0	0.60	2.10	70.7	12.2	50	–
32/8	32.0	8.0	0.70	2.40	106.0	12.2	50	–
52/13	52.0	13.0	0.70	2.40	156.0	12.2	30	–



Standard colour				
0 = black				



Remarks:
– Cut lengths – printed on request – with a surcharge
– Air-filled up to size 12/3
– Certifications available with a surcharge
– Technical data pages 44-45
Subject to alteration.
*Outer Jacket

Safety warning:

For work involving electric tensions of more than 48 V, insulating, connecting, repairing, and water-proofing electrical components should only be carried out by qualified electricians.