

DERAY®-I










- 55° to + 135° C

Flexible

Heat-shrinkable sleeve -
Modified polyethylene
Radiation crosslinked
Insulation class B (VDE 05 30)

A brilliant variety of function and colour. DERAY-I is a universal heat-shrinkable sleeve type with excellent physical and chemical properties: flexible, non-meltable, quick shrinking and continuous temperature resistant up to 135° C. Applications: insulation, corrosion and mechanical protection, bundling, marking, bending protection, strain relief etc.

Ordering size in inches	Diameter as supplied min. d2 mm	Diameter fully recovered max. d1 mm	Wall thickness as supplied S2 appr. mm	Wall thickness fully recovered S1 appr. mm	Weight colour type A max. g/m	Weight transparent type B max. g/m	Delivery units		
							lengths of 1,22 m	spool m	mini spool m
3/64	1.2	0.6	0.20	0.40	2.2	1.6	30.5	300	150
1/16	1.6	0.8	0.20	0.40	2.7	2.0	30.5	300	150
3/32	2.4	1.2	0.25	0.50	3.8	2.9	30.5	300	150
1/8	3.2	1.6	0.25	0.50	4.8	3.6	30.5	300	150
3/16	4.8	2.4	0.25	0.50	6.6	5.0	30.5	300	75
1/4	6.4	3.2	0.30	0.60	10.5	7.8	12.2	300	75
3/8	9.5	4.8	0.30	0.60	14.6	11.0	12.2	150	75
1/2	12.7	6.4	0.30	0.60	19.0	14.5	12.2	100	50
3/4	19.0	9.5	0.40	0.80	38.0	25.1	12.2	50	30
1	25.4	12.7	0.45	0.90	51.4	38.9	12.2	50	30
1 1/4	31.8	15.9	0.45	0.90	68.2	50.4	-	50	30
1 1/2	38.0	19.0	0.50	1.00	87.0	65.8	-	50	30
2	51.0	25.4	0.55	1.10	129.0	97.3	-	50	30
3	76.0	38.0	0.65	1.30	211.0	160.0	-	25	15
4	102.0	51.0	0.70	1.40	311.0	235.0	-	25	15
25*	2.5	0.8	0.15	0.40	-	-	-	300	-
40*	4.0	1.6	0.20	0.50	-	-	-	300	-
56*	5.6	2.4	0.20	0.50	-	-	-	300	-
81*	8.1	3.2	0.20	0.60	-	-	-	300	-
110*	11.0	4.8	0.25	0.60	-	-	-	150	-
150*	15.0	6.4	0.25	0.60	-	-	-	100	-



Standard colours						Special colours (on request)			
0 = black	2 = red	4 = yellow	6 = blue	9 = white	99 = transp.	1 = brown	3 = orange	5 = green	7 = violet
spool, mini spool	mini spool								
Delivery units									

- Remarks:
- Cut lengths - printed on request - with a surcharge
 - Air-filled up to size 1/2"
 - Certifications available with a surcharge
 - Certifications possible only for sizes measured in inches (apart from 11/4" for VG)
 - Sizes marked with * only available in black
 - Technical data pages 40-41 Subject to alteration.

