



DERAY®-PTFE









- 65° to + 260° C

* (Teflon®) Semi-rigid
Heat-shrinkable sleeve – PTFE
Insulation class C (VDE 05 30)

When the going gets tough, DERAY-PTFE gets going.

This non-combustible, thin-walled, semi-rigid heat-shrinkable sleeve is extremely resistant to high temperatures and chemicals. This transparent sleeve type is well suited for insulating and protecting components subject to extreme chemical and thermal loads.

Ordering size		Diameter as supplied min. d2 mm	Diameter fully recovered max. d1 mm	Wall thickness as supplied S2 appr. mm	Wall thickness fully recovered S1 appr. mm	Delivery units		
2:1 AWG	4:1 inches					lengths of 1,22 m	spool m	mini spool m
30		0.86	0.38	0.12	0.23	30.5	-	-
28		0.97	0.46	0.12	0.23	30.5	-	-
26		1.17	0.56	0.12	0.23	30.5	-	-
24		1.27	0.64	0.13	0.25	30.5	-	-
22		1.40	0.80	0.13	0.25	30.5	-	-
20		1.52	0.97	0.15	0.30	30.5	-	-
18		1.93	1.17	0.15	0.30	30.5	-	-
16		2.36	1.45	0.15	0.30	30.5	-	-
14		3.05	1.82	0.15	0.30	30.5	-	-
12		3.81	2.26	0.15	0.30	30.5	-	-
10		4.85	2.80	0.15	0.30	30.5	-	-
8		6.10	3.55	0.19	0.38	12.2	-	-
6		7.67	4.40	0.19	0.38	12.2	-	-
4		9.40	5.45	0.19	0.38	12.2	-	-
2		10.92	6.90	0.19	0.38	12.2	-	-
0		11.94	8.56	0.19	0.38	12.2	-	-
	5/64	1.98	0.64	0.06	0.23	30.5	-	-
	3/32	2.36	0.80	0.06	0.25	30.5	-	-
	1/8	3.18	0.94	0.06	0.25	30.5	-	-
	3/16	4.76	1.27	0.08	0.30	30.5	-	-
	1/4	6.35	1.60	0.08	0.30	12.2	-	-
	3/8	9.52	2.44	0.08	0.30	12.2	-	-
	1/2	12.70	3.66	0.10	0.38	12.2	-	-
	5/8	15.88	4.52	0.10	0.38	12.2	-	-
	3/4	19.05	5.70	0.10	0.38	12.2	-	-
	1	25.40	7.06	0.10	0.38	12.2	-	-
	1 1/4	31.75	8.82	0.10	0.38	12.2	-	-



Standard colour				Special colour (on request)			
99 = transparent				0 = black			

* ® = registered trademark of Du Pont for the raw material

Remarks:
- Cut lengths – printed on request – with a surcharge
- Technical data pages 42-43
Subject to alteration.

