

**Fax-on-Demand:** (800) 260-9099  
(650) 361-6523

| FAX ID | Description |
|--------|-------------|
| 2030   | Data sheet  |

# DCPT

Flexible, flame-retardant, dual-color polyolefin tubing

Before ordering check with factory for most current data.

## Applications

Used to identify "ground" on wires and in cables, and to jacket and insulate light-duty harnesses. Easily marked by conventional techniques for additional identification of wire and cable.

## Operating Temperature Range

-55°C to 135°C

## Features/Benefits

- 2:1 shrink ratio.
- Dual colors (yellow/green) for instant identification.
- Co-extrusion of tubing colors, giving color permanence superior to that of conventional ink marking.
- Flame-retardance.
- Flexibility: able to conform to irregular shapes.
- Excellent physical, chemical, and electrical properties that meet industry standards for highly reliable, general purpose tubing.

## Installation

Minimum shrink temperature: 95°C

Minimum full recovery temperature: 120°C



## Specifications/Approvals



| Series | UL                     | CSA                     | Military   | Agency  | Raychem |
|--------|------------------------|-------------------------|--|---|---------|
| DCPT   | E35586<br>600 V, 125°C | LR31929<br>600 V, 125°C | Def Stan 59-97 Issue 3 Type 2B<br>VG 95343 Pt 5 Type A | AFS 2270<br>DIN 29807<br>VDE 0341<br>Pt 9005 Type A | RW-2056 |

## Product Dimensions (mm/in)

| Size          | Inside diameter                    |                                       | Wall thickness<br>Recovered<br>after heating* |
|---------------|------------------------------------|---------------------------------------|---|
|               | Minimum<br>expanded<br>as supplied | Maximum<br>recovered<br>after heating |   |
| 3/1.5 (1/8)   | 3 (.118)                           | 1.5 (.039)                            | 0.51 ±.10 (.020 ±.004)                        |
| 6/3 (1/4)     | 6 (.236)                           | 3.0 (.118)                            | 0.58 ±.10 (.025 ±.004)                        |
| 8/4 (3/8)     | 8 (.315)                           | 4.0 (.158)                            | 0.64 ±.10 (.025 ±.004)                        |
| 10/5 N/A      | 10 (.394)                          | 5.0 (.197)                            | 0.64 ±.10 (.025 ±.004)                        |
| 12/6 (1/2)    | 12 (.472)                          | 6.0 (.236)                            | 0.64 ±.10 (.025 ±.004)                        |
| 19/9 (3/4)    | 19 (.748)                          | 9.0 (.354)                            | 0.76 ±.12 (.030 ±.005)                        |
| 26/13 (1)     | 26 (1.024)                         | 13.0 (.512)                           | 0.89 ±.12 (.035 ±.005)                        |
| 38/19 (1 1/2) | 38 (1.500)                         | 19.0 (.748)                           | 1.00 ±.12 (.039 ±.005)                        |

\*Wall thickness will be less if tubing recovery is restricted during shrinkage.

## Ordering Information

|                      |   |
|----------------------|---|
| Color                | Standard Yellow/green stripe (-45)  |
| Size selection       | Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request. |
| Standard packaging   | On spools.  |
| Ordering description | Specify product name, size (metric or inches), and color (for example, DCPT 8/4-45).  |