

Raychem

EPKE

**Heat-shrinkable End Seals for
MI/MIND paper or plastic
insulated cables up to 1 kV**





EPKE Heat-shrinkable End Seals for MI/MIND paper or plastic insulated cables up to 1 kV

Raychem End Seals are used all over the world for sealing and insulating the ends of cables maintained under power, prior to further network extension. The unusually rapidly and reliably achieved moisture seal has been proven in thousands of installations and results from the heat-shrinkable design and special precoated adhesives. Although light in weight and easy to install anywhere, End Seals also resist impact, eliminate topping-up and curing delays and can be immediately buried and taken into use.

The heat-shrinkable properties also mean each End Seal kit can be installed on several different cable sizes and constructions without the need for special tools or skills. Supplied complete with precise application information and illustrated instructions, a limited number of these versatile kits covers the entire range of paper and plastic cables for 1 kV.

The unlimited shelf-life simplifies stock-keeping even more.

Raychem End Seals combine these advantages with resistance to soil chemicals and the environment in a heat-shrinkable material with outstanding insulating performance. They are yet another result of the unique experience of Raychem in the application of radiation cross-linked polymers to power engineering.

Raychem is the leading manufacturer of heat-shrinkable materials and one of the largest cable accessory makers. A wide range of terminating, jointing and repair systems, tubings and mouldings is available, supported by world-wide customer service and technical assistance to meet the demands of the growing world of energy.

**Heat-shrinkable
End Seals for MI/MIND
paper or plastic insulated
cables up to 1 kV**

Minimum performance for Raychem End Seals

Test sequence		Result
Insulation resistance	between conductor and grounded water bath	>1000 MΩ
Impact	4 kg weight dropped twice from 2 m	pass
A.C. Voltage Withstand	4 kV for 15 min	pass
Impulse Voltage Withstand	10 positive and 10 negative, 1.2/50 μs, 8 kV peak, between conductor and grounded water bath	pass
Insulation Resistance		as above >1000 MΩ
D.C. Voltage Withstand	15 kV for 5 min	pass
Notes:	1. All voltages are phase to ground. 2. Further details are given in Raychem specification PPS 3013.	

Ordering information

Raychem End Seals are available for paper insulated cables with 2 to 4 cores and plastic insulated cables with 1 to 5 cores up to 1 kV and 300 mm A full selection table is available on request.

For further details on this or any other Raychem products please contact your local Raychem sales engineer.

At Raychem we are committed to continuous quality improvement in every aspect of our business.

All above information, including drawings, illustrations and graphic displays, reflects our present understanding and is to the best of our knowledge and belief correct and reliable. It does, however, under no circumstance constitute an assurance of any particular qualities. Such an assurance is only provided in the context of our product specifications. Our liability for this product is set forth in our standard terms and conditions of sale. Raychem is a trademark of Raychem Corporation.

**Raychem Corporation
Electrical Products Division**
300 Constitution Drive
Menlo Park, CA 94025, U.S.A.
Tel. (415) 3 61-31 36
Fax (415) 3 61-50 43

**Raychem Corporation
Electrical Products Division**
220 Lake Drive
Newark, DE 19702, U.S.A.
Tel. (800) 3 27-69 96
Fax (800) 5 27-83 50

**Raychem Ltd.
Electrical Products Division**
Faraday Road
Dorcan, Swindon
Wiltshire SN3 5HH, U.K.
Tel. (0 17 93) 52 81 71
Fax (0 17 93) 57 24 03

**Raychem GmbH
Electrical Products Division**
Haidgraben 6
85521 Ottobrunn
Munich, Germany
Tel. (0 89) 60 89 - 0
Fax (0 89) 609 63 45