

SFR

Very flexible, flame-retardant silicone elastomer tubing

Fax-on-Demand: (800) 260-9099
(650) 361-6523

FAX ID	Description
2190	Data sheet
2191	RW-3011

Before ordering check with factory for most current data.



Applications

Provides cable jacketing, harness protection, and strain relief for electronic components, semiconductor leads, and wire splices. Ideal for applications that require flexibility over a wide range of operating temperatures.

Operating Temperature Range

-75°C to 180°C

Features/Benefits

- Outstanding low-temperature flexibility.
- Resistance to hydraulic fluids, fuel, and lubricating oils.
- Very good ablative characteristics: when exposed to flame, surface turns to insulative char or "ablates."

Installation

Minimum shrink temperature: 135°C

Minimum full recovery temperature: 175°C

Specifications/Approvals

Series	Military	Raychem
SFR	MIL-DTL-23053/10* MIL-R-46846, Type II, Class 1	RW-3011

*Formerly MIL-I-23053/10.

Product Dimensions (mm/in)

Size	Inside diameter		Wall thickness Recovered after heating**	Size	Inside diameter		Wall thickness Recovered after heating**
	Minimum expanded as supplied	Maximum recovered after heating			Minimum expanded as supplied	Maximum recovered after heating	
1/4	6.4 (.250)	3.6 (.143)	0.88 ±.25 (.035 ±.010)	1	25.4 (1.000)	14.5 (.570)	1.77 ±.51 (.070 ±.020)
3/8	9.5 (.375)	5.4 (.214)	1.02 ±.25 (.040 ±.010)	1 1/4	31.8 (1.250)	18.1 (.714)	2.21 ±.51 (.087 ±.020)
1/2	12.7 (.500)	7.3 (.286)	1.21 ±.38 (.048 ±.015)	1 1/2	38.1 (1.500)	21.8 (.857)	2.41 ±.51 (.095 ±.020)
5/8	15.9 (.625)	9.1 (.357)	1.32 ±.38 (.052 ±.015)	1 3/4	44.5 (1.750)	25.4 (1.000)	2.71 ±.51 (.107 ±.020)
3/4	19.1 (.750)	10.9 (.428)	1.44 ±.38 (.057 ±.015)	2	50.8 (2.000)	29.0 (1.140)	2.79 ±.51 (.110 ±.020)
7/8	22.2 (.875)	12.7 (.500)	1.65 ±.38 (.065 ±.015)				

**Wall thickness will be less if tubing recovery is restricted during shrinkage.

Ordering Information

Color	Standard Black (-0)
Size selection	Always order the largest size that will shrink snugly over the component to be covered. Special order sizes are available upon request.
Standard packaging	On spools.
Ordering description	Specify product name, size, and color (for example, SFR 1/4-0).